



Greater opportunities for small businesses - Slican IPM-032

Do you run a small business? Do you care for technologically advanced telecommunications solutions? We have the solution for you - SLICAN IP PBX IPM-032. Due to the uniform, advanced IT platform, provides a cheap VoIP communication right from the basic product version. IP PBX IPM-032 is a universal system, that will grow with your company.

Telephone exchanges IPM-032 are characterized by flexibility and modular structure. Whole system is extended by its own and external applications, creating a complete system of cheaper and safe telecommunications for success oriented companies.



IPM-032.WM

IPM-032.2U

- VoIP
- ISDN
- LAN
- GSM
- USB



INTEGRATION

IP PBX IPM-032 is CTIP, XML, HTTP, HOTELP, TAPI and EdbRECP protocol. It allows you integration with variety of other applications, where the added value is a professional software deployment without incurring the additional investment costs. Slican CTI Communicator is a set of intuitive solutions on computers and smartphones. Slican TAPI – Slican PBX-es cooperating with MS Outlook® application.



NETWORKING

IP PBX IPM-032 will allow your company flexible expansion of the telecommunications system. Networking with other Slican IP PBX-es up to 3999 subscribers enables almost unlimited configuration of telecommunications system according to the needs of your business.



COST CONTROL

Online support allow you to apply cost saving policy for your company, associated with programming and PBX service. LCR (Least Cost Routing) solution, billing applications, ensure the lowest bills and cost control.



WORK ORGANIZATION

Slican RecordMAN application suite provides professional business record and management of calls. Using the teleconference provides better organization of work within the company. INVENIO Infolines provide flexible navigation that will help callers a fast connection to the department of the company.



Greater opportunities for small businesses - Slican IPM-032

		IPM-032.A6x4.WM	IPM-032.A8x4.2U
Maximal capacity	Analogue ports AB (FXS)	24	32
	Analogue trunks POTS (FXO)	12	16
	ISDN BRA (int. or ext.)	12	16
	E 1 / ISDN PRA (int. or ext.)	2	2
	IP channels	8 / 32	8 / 32
	IP trunks (SIP)	100	100
	IP subscribers (SIP)	100	100
	GSM trunks	12	16
	CTS system ports (Up ₀ + IP)	124	124
	Calls recording channels	12	12
	SD memory cards	1	1
Available devices	Slican system phones CTS (Up ₀ / IP) ¹		
	IP phones (SIP)		
	Analog phones		
	hot line Slican phone HLP-22		
	Slican consoles		
	Slican DPH series door phones		
	Multi Switch Box (MSB-1102) and Multi Audio Box (MAB-1101)		
Applications supporting IPM-032	Slican CTI Communicator - MessengerCTI and WebCTI		
	Slican BillingMAN / BillingMAN.plus		
	Slican RecordMAN.server / RecordMAN.client		
VoIP parameters	Supported protocols	eSSL, SIP 2.0 codecs G.711 a l μ - standard, G.729- option	
	Working mode	VoIP master or / and slave	
Protocols	Voice communication protocols	POTS / ISDN-EDSS1 / QSIG / SIP 2.0 / GSM900 / 1800 / 2100 / Up ₀	
	Server communication protocols	CTIP / HOTELP / TAPI / EbdRECP / HTTP / XML	
Power supply	~110-230V;50-60 Hz; < 150 VA		
Buffer power supply	option		

¹ Request firmware compatibility

The presented material is for information purposes. In order to properly configure of PBX, we recommend contact and consultation with Slican Distributor / Reseller.