



## Best communication for your business Slican IPU-14

IP PBX Slican IPU-14 is a product that perfectly meets the needs of small business in modern, multi-task telecommunication. Great price, access to all way of communication and modular build are few of the many advantages of IP PBX Slican IPU-14. There are 4 free slots that allow to install the necessary equipment at a convenient time for the company. Built-in GSM and VoIP gateways, the ability to record calls, and a free Slican BillingMAN application provide cheap and high quality communications. Choosing multifunctional Slican solutions, you can significantly reduce expenses. Now all that is needed for effective communication is in the IPU-14 IP PBX. Aesthetic design, small size and the ability to hang on the wall or RACK (1U) mounted version are also the advantages of the IP PBX.



- VoIP
- ISDN
- LAN
- GSM
- USB

IP PBX IPU-14



### VoIP TELEPHONY

Small business can connect now up to 24 IP subscribers. This is a special offer at a reasonable price. Configuring of product and creating a communication system has become even more flexible, according to the needs.



### GSM GATEWAY

Built-in GSM gateway provides higher call quality and greater reliability, compared to external devices. IPU-14 IP PBX offers up to two GSM lines, PBX can be used in corporate GSM network, realizing cheap mobile calls.



### COST CONTROL

Slican BillingMAN application which is in the PBX price, connections through a cheap VoIP network or LCR (Least Cost Routing choice) guarantee the lowest bills and cost control. Additionally WebCTI application that is complementary to applications MessengerCTI allows for example access to call history and phone settings. WebCTI allows the manager to identify and assign quote limits on calls for each employee.



### WORK ORGANIZATION

Good organization of work is the basis for the proper functioning and development of the company. Recording and archiving of calls or quick access to information related to the customer in the CRM system, will make work easier. Flexible Slican INVENIO infolines help your customers contact to your company. Using the conference will facilitate effective consultation and quick decision making. MessengerCTI provides reliable and comfortable voice and text communication. IP PBX Slican IPU-14 works with door phones and Slican DPH access control system. Through the PBX you can also control the heating, building lighting or other devices.



## Best communication for your business Slican IPU-14

		IPU-14.103.WM	IPU-14.105.WM / IPU-14.105.1U
Maximum capacity	Analogue ports AB (FXS)	14	14
	Analogue trunks POTS (FXO)	4	5
	ISDN BRA (only external)	4	4
	IP channels	8	8
	IP trunks (SIP)	16	16
	IP subscribers (SIP)	24	24
	GSM trunks	2	2
	CTS system ports (Up <sub>0</sub> + IP)	28	28
	Calls recording channels	8	8
	MicroSD memory cards	1	1
	SN / RL ports	2 / 2	2 / 2
Available devices	Slican system phones (Up <sub>0</sub> / IP) <sup>1</sup>		
	IP phones (SIP)		
	Analog phones		
	Slican HLP-22 hot line phone		
	Slican consoles		
	Slican DPH series door phones		
	Multi Switch Box (MSB-1102) and Multi Audio Box (MAB-1101)		
Applications supporting IPU-14	Slican CTI Communicator – MessengerCTI and WebCTI		
	Slican BillingMAN / BillingMAN.plus		
	Slican RecordMAN.server / RecordMAN.client		
	Slican ConfigMAN.admin / ConfigMAN.user		
VoIP parameters	Supported protocols	eSSL, SIP 2.0 kodek G.711a	
	Working mode	klient lub / i serwer VoIP	
Protocols	Voice communications	POTS / ISDN-EDSS1 / QSIG / SIP 2.0 / GSM900 / 1800 / 2100 / Up <sub>0</sub>	
	Server communications protocols	CTIP / HOTELP / TAPI / EbdRECP / HTTP / XML	
Port Ethernet 10 / 100		1	
Port USB (for service)		1	
Power supply		~230 V ± 10%, 50Hz	
Power consumption		22 W	
Dimensions (mm) width x height x depth		WM: 210 x 301 x 55 mm; 1U: 483 x 310 x 45 mm	
Weight		WM: 1,60 kg; 1U: 3,65 kg	

<sup>1</sup>Slican CTS-202.IP system phone does not work with PBX IPU series, CTS-330.CLBT and CTS-330.IPBT works with 6.30.0060 firmware or higher, CTS-220 works with 6.50 firmware or higher

The presented material is for information purposes. In order to properly configure of PBX, we recommend contact and consultation with Slican Distributor / Reseller