



Digital door phone systems Slican HAS-3000T and HAS-3032

Looking for door phone for home, company or group of buildings? Check it - Slican HAS door phone system. Comfortable door phone solution - designed to full fill requirements of private and business users!

Slican HAS series door phone are available in two models:

HAS-3000T supports single entry and HAS-3032 supports several entrances to the building.

HAS-3000T version is available with the RFID reader to facilitate access to the building.

Door phones in both versions are offered in several models of cassettes to choose. The housings of the cassettes with the control panel both in the flush-mounted version and in the surface-mounted versions, are made of high quality materials, durable and resistant to atmospheric conditions and mechanical damage.



UNIVERSAL

The system is designed for individual and multi-family housing, businesses and office buildings. The elegant and on the same time resistant steel casing, a versatile intercom uniphone HAS-255 perfectly use the new trends in construction.



COMFORT

Tenant does not have to carry key to the door, selects only the code on the keypad. Uses legible and illuminated keyboard (best appreciated at night). Choice of number (the buttons) is confirmed by a signal light and sound.



SECURITY

The system allows communication with people who have not yet the building / offices. It guards against unauthorized guests, and those that interfere peace of mind. Owner has also the power to change the combination if it was announced to third party persons.



ECONOMY

The customer does not bear the costs of refurbishing the existing intercom network - does not need replacement of an existing installation and wiring.



UNIQUENESS

Unique solution for residential homes, both single-and multifamily. HAS-3032 will provide connectivity between multiple entrances / gates with concierge.



Digital door phone systems Slican HAS-3000T and HAS-3032

PARAMETERS

| System | HAS-3000T | HAS-3032 | |
|--|---|---|--|
| Connection with other HAS system | NO | YES (max. 32 cassettes) | |
| System capacity | up to 255 premises / uniphones | <ul style="list-style-type: none"> single gate system - up to 255 premises / uniphones multi gates system - capacity up to 128 premises / uniphones per one cassette and up to 500 premises / uniphones for all cassettes, up to 32 cassettes | |
| Keypad type | tactile keypad | | |
| Display | LED red color | | |
| Installation | two wires bus | four wires cables between cassettes | |
| Power supply | 12V~ or 12V= | | |
| Required additional equipment | NO | | |
| Supplementary Slican products | UNIPHONE US.P2L-HAS255 | | |
| Montage | flush-mounted version / surface-mounted versions | | |
| Cover characteristic | KD12P/KD12N* | HR12P/HR12N | VE12P/VE12N |
| P - flush-mounted version N - surface-mounted version | <ul style="list-style-type: none"> stainless steel powder coated sheet steel graphit colour | <ul style="list-style-type: none"> front panel made of stainless steel INOX cassette of stainless steel powder (with a frame of stainless steel INOX in surface-mounted version) | <ul style="list-style-type: none"> front panel made of stainless steel INOX cassette of stainless steel powder (with a frame of stainless steel INOX in surface-mounted version) |
| Dimensions of cassette (in millimeters) | P 176 x 212 x 34 N 178 x 214 x 63 | 165 x 194 x 40 178 x 214 x 66 | 325 x 88 x 40 338 x 104 x 66 |

FUNCTIONALITY

- one HAS-3000T cassette serves one gate - entrance
- maximal connection up to 32 of HAS-3032 cassettes with voice connection ability
- possibility of establishing bi-directional call – numbers can be dialed both, from uniphones and from cassette
- two independent control outputs (door and gate controlling) - independent opening of both exits - from uniphone and from cassette
- assigning users individual code (PIN) which enables access to building automatically or manually
- audio signaling also if uniphone handset is incorrectly hang up
- complete installation errors identification (incorrect uniphone connecting, incorrect programming, etc).
- user menu protected with special access procedure
- possibility of connecting auxiliary external calling button, door phone calls are routed to guardian or front desk
- PIN settings automatic or manual for each premises
- working temperature range - from -25°C up to +55°C
- individually selectable two ringing volume levels
- „Dallas” key reader - only for HAS-3000T
- VIP user function – high entrance privileges – only for HAS-3032

* HAS-3032-KD12 available only in KD12P cassette (flush-mounted version)