



Comfortable system phones Slican CTS-220

Multi-functional, pleasant to use, easy to install Slican system phones. You can choose classical model CTS-220.CL or VoIP phone – CTS-220.IP with the possibility of installing the WiFi.



CTS-220.CL / 220.IP



CTS-220.CL / 220.IP with CTS-338 console

Phone profile is created and stored in the Slican PBX memory. The phone can be used immediately after power connection, without complicated and time-consuming programming. Programmable BLF buttons allow you to create individual functions, services or create a list of handy contacts. For your comfort and to increase number of programmable keys, you may connect to each Slican CTS-220 system phone series up to 4 CTS-338 consoles. With consoles you may program up to 162 buttons.



COMFORT OF WORK

Legible and large back lighted LCD display with adjustable contrast, will make use of your phone more convenient. Properly shaped and light handset and high sound quality, guarantee user satisfaction. Friendly menu and navigation keys allow you to use quickly full range of system phone's functions. Programmable buttons can be assigned to a number of functions, services or phone numbers.



FUNCTIONALITY

Slican CTS-220 system phones are designed to work with Slican:¹ NCP, IPL-256, IPM-032, IPU-14, IPS-08 (only CTS-220.IP), MAC-6400 PBX-es. CTS-220 will tell you what is duration of your call and how much it costs. Handy information about incoming calls, dialed numbers, missed calls allows you organize your work much more efficient. Access to the two phone books (public and private), and internal numbers list allows fast communication with selected subscriber.



MORE POSSIBILITIES

CTS-220.IP can be installed and used wherever there is Internet connection. Additional advantage is PoE (Power over Ethernet) standard, you can also install a WiFi module.



Comfortable system phones Slican CTS-220

SOUND	CTS-220.CL	CTS-220.IP
"Hands Free" system	YES	YES
Ringtones	YES - 5	YES - 5
Individual doorphone ringtone	YES	YES
Continuous volume control and audio sounds	YES	YES
DISPLAY AND USER INTERFACE		
Monochromatic display	2,8"	2,8"
Text rows / Text menu	5 - ROW	5 - ROW
Time, day, date presentation	YES	YES
Presentation of call duration and costs during and after call	YES	YES
Handy list of outgoing / received / missed calls	YES	YES
Display menu language	PL / EN / GER	PL / EN / GER
Possibility to implement local language	YES	YES
KEYBOARD		
Menu keys / up / down / arrows	YES	YES
Programmable keys	YES - 8	YES - 8
Main function / operation keys	Flash / SPK ON / SPK OFF / MUTE / REDIAL	Flash / SPK ON / SPK OFF / MUTE / REDIAL
Loudspeaker key	YES	YES
Possibility of using headphones	YES	YES
CALL AND CONTACTS FEATURES		
Phone books – public and private – as well as extension numbers list	YES	YES
Optical signaling of incoming and missed calls	YES	YES
Auto-redial function – automatic call repeat	YES	YES
List of dialed, received and missed calls	YES	YES
Presentation of dialed number and incoming call number	YES	YES
Service of mobile subscribers - Slican MobilePhone and Slican CallBack	YES	YES
Call recording – Slican Embedded Recording	YES	YES
Phone – lock (private PIN code to use phone)	YES	YES
PBX SERVICES		
Conference Calls and three-way Calling	YES	YES
Internal numbers and outgoing lines busy status optical signaling	YES	YES
Voice mail	YES	YES
CLIR and temporary CLIR	YES	YES
Information about waiting call	YES	YES
Manual Call forwarding	YES	YES
Automatic call forward when busy or absence	YES	YES
Anonymous and malicious call blocking (MCID)	YES	YES
„Do not disturb" function	YES	YES
Music on Hold	YES	YES
Door phone function – door opening	YES	YES
Intercom configuration (example: for secretary)	YES	YES
Automation control	YES	YES
TECHNICAL DATA		
Power supply from PBX / option – power supplier 12V/1A	YES	YES
Color	GREY / BLACK	GREY / BLACK
SWITCH – two-port LAN switch	-	YES
Handset jack with microphone (socket RJ9) (max. headphones impedance - 40 Ohm)	YES	YES
WiFi module (NCP – firmware 1.12 or higher, IPx, MAC, CCT – firmware 6.54 or higher)	-	OPTION
RELATED PRODUCTS		
Slican PBX-es ¹ : NCP, IPL-256 / IPM-032 / IPU-14 / IPS-08 ² / MAC-6400	YES	YES
Cooperation with CTS-338 console	YES-MAX 4 CONSOLES	YES-MAX 4 CONSOLES

¹ Slican PBX-es - NCP fw 1.06 is required, IPx and MAC - fw 6.50 or higher is required, ² CTS-220.IP only