



Smart and functional business phone Slican CTS-330

System phone for companies which require sophisticated phone system and effective call and contact managing. Several models to choose – classical model – CTS-330.CL, IP system phone – CTS-330.IP.



CTS-330

CTS-330 with CTS-338 console

Phone profile is created and stored in Slican PBX memory. Phone can be used immediately after switching it on, without complicated and time consuming configuration. Programmable BLF buttons allow you to create individual functions, services or create a list of handy contacts. For your comfort and to increase number of programmable keys, you may connect to each Slican CTS-330 system phone series up to 4 CTS-338 consoles. With consoles you may program up to 170 buttons.



Phone is equipped in high quality color, touch screen which ensures perfect visibility in different lighting conditions. Due to perfect voice quality and simple maintenance make this phone smart tool for every day work. Programmable touch and standard buttons of CTS-330 enable to function creation, services or contact.



System phones Slican CTS-330 are designed to work with Slican NCP system and IPL-256, IPM-032 and IPU-14 PBX-es. CTS-330 will tell you what is duration of your call and how much it costs. Handly information about incoming calls, dialed numbers and missed calls allows you organize your work much more efficient. Access to the two phone books (public and private) and internal numbers list allows fast communication with selected subscriber.



Slican CTS-330.IP system phone can be installed and used wherever there is Internet connections. Additional advantage is PoE (Power over Ethernet) standard.





Smart and functional business phone Slican CTS-330

SOUND	CTS-330.CL	CTS-330.IP
"Hands Free" system	YES	YES
Ringtones	YES - 10	YES - 10
Individual doorphone ringtone	YES	YES
Continuous volume control and audio sounds	YES	YES
DISPLAY AND USER INTERFACE	1	
High quality color, touch TFT screen (480 x 272 pixels)	YES	YES
Adjustmen of display brightness	YES - 12 levels	YES - 12 levels
Time, day, date presentation	YES	YES
Presentation of call duration and costs call	YES	YES
Handy list of outgoing / received / missed calls	YES	YES
Display menu language	PL / EN / GER	PL/EN/GER
KEYBOARD		
Navigation key for direct function selection	YES	YES
Programmable keys	YES - 19	YES - 19
	Flash / SPK ON / SPK OFF/	Flash / SPK ON / SPK
Main function / operation keys	MUTE / REDIAL	OFF/ MUTE / REDIAL
Loudspeaker key	YES	YES
Possibility of using headphones	YES	YES
CALL AND CONTACTS FEATURES	125	TES
Phone books – public and private – as well as extension numer list	YES	YES
Optical signaling of incoming and missed calls	YES	YES
Auto – redial function – automatic call repeat	YES	YES
List of dialed, received and missed calls	YES	YES
Presentation of dialed numer and incoming call number	YES	YES
Service of mobile subscribers - Slican MobilePhone and Slican CallBack	YES	YES
	YES	YES
Call recording - Slican Embedded Recording Phone – lock (private PIN code to use phone)	YES	YES
	123	TES
PBX services	VEC	VEC
Conference calls and three-way calling	YES	YES
Internal numbers and outgoing lines busy status optical signaling	YES	YES
Voice mail	YES	YES YES
CLIR and temporary CLIR		YES
Information about waiting call	YES	-
Manual Call forwarding	YES	YES
Automatic call forward when busy or absence	YES	YES
Anonymous and malicious call blocking (MCID)	YES	YES
"Do not disturb" function	YES	YES
Music on Hold	YES	YES
Door phone function – door opening	YES	YES
Intercom configuration (example: for secretary)	YES	YES
Automation control	YES	YES
TECHNICAL DATA		
Power supply from PBX / option – power supplier 12V/1A	YES	YES
Color	BLACK	BLACK
Headphones jack with microphone (mini-jack) (max. headphones impedance -	YES	YES
40 Ohm)		
SWITCH – two-port LAN swith	NO	YES
Bluetooth module	NO	NO
RELATED PRODUCTS		
Slican PBX-es: NCP/ IPL-256 / IPM-032 / IPU-14 / MAC-6400	YES	YES
Cooperation with CTS-338 console	YES-MAX 4 CONSOLES	YES-MAX 4 CONSOLES
Comunicator Slican MessengerCTI	YES	YES
Slican MobilePhone and Callback, Embedded Recording, TAPI/CTIP protocols	YES	YES